



PEBBLITE

POROUS PAVING



Porous Paving for:-

- Stairways
- Tree Pits
- Garden Beds & Planters
- Roof Top Gardens
- Displays
- Pathways

- Natural & Coloured Hues
- Attractive, Slip Resistant Finish
- Durable Hard Wearing Surface
- Porous Finish
- No Loose Pebbles



Website: www.omnicrete.com.au


Pebblite is an environmentally friendly, decorative, UV stable, porous paving surface for the aesthetic enhancement of landscape environments. Pebblite has applications as a porous bound mulch for tree pits and gardens and is ideally suited for landscape projects where a decorative porous paving system is preferred.

By utilising Pebblite porous paving rainwater is able to soak through to the soil which in turn:

- increases groundwater recharge by allowing the water to soak through the soil
- improves stormwater quality by filtering stormwater and reducing pollutant loads
- reduces erosion and habitat scouring

Available in a wide range of natural and synthetic colour finishes, Pebblite surfacing provides for a surfacing system that is:

- aesthetically pleasing
- yellowing resistant & UV stable
- trafficable & durable
- permeable to air and water
- fast curing with minimal disruption



For further specification details contact:-



Toll Free: 1300 851 523

International: +61 3 9469 4498

Email: info@omnicrete.com.au

Website: www.omnicrete.com.au

Installation

Pebblite is generally installed to depths between 30mm and 100 mm dependent upon the type and extent of expected traffic and may be installed to any firm sound substrate with adequate sub surface drainage including direct application over existing concrete or asphalt.

General application within the landscape environment encompasses installation to existing earth works and to ensure optimal drainage. Pebblite should be applied to a well prepared sub base and the inclusion of agricultural drainage pipes in the base gravel layer is an option in areas where excessive run off may be expected.

Installation to garden beds and tree pits should be undertaken in consultation with horticultural specialists and should be installed at prescribed depths as recommended by horticultural specialists taking into account root depth and specific plant species requirements.

The Pebblite surfacing material is obtained by combining suitably graded clean dry aggregate with the SureStone binding resin. Resin is batched by weight, added to clean dry aggregate and mixed thoroughly in a suitable mixing vessel until the aggregate has been completely wetted out.

Once mixed the material should be transferred to the application area and trowelled into the suitably prepared application area to achieve a uniform level finish.

A tack free cure is generally achieved in 8 - 12 hours and the surfacing may be opened to general trafficking.

APPROVED INSTALLER:-